

Published: 04/02/69

Identification

Specification for Maintenance Binder
D. R. Vinograd

Purpose

The following is a specification of an interim binder command for use primarily by maintenance on Multics. It is not intended to be clean, easy to use, or fast, just quick to implement. It is suggested that anyone who does not like it, may if he chooses, come up with a new design and if approved he can recode it.

Specification

The binder command is called with a single argument, the path name of an archive file containing the object programs to be bound together. The name of the archive file (e.g., gamma or gamma.archive) will be the primary name of all files that the binder creates. The following files will be created by the binder:

gamma	This segment will have the names of all files in gamma.archive in addition to the name gamma
gamma.map	(which contains only the map of the bound segment)

The path name specified to the binder may be the working directory or not, in either case the created files will be placed in the caller's working directory. The files to be bound must be contained in the archive file specified and must be object type files. The trailing suffix ".archive" is not specified in the path name. For example, if the user desired to rebind segment alpha which is contained in the bound segment gamma which already exists in the library he would proceed as follows:

1. Make a copy in his working directory of the file gamma.archive
2. Convert to object format the segment alpha and archive it in the segment gamma.archive

3. Run the bind command as

```
bind gamma
```

At the completion of this command his working directory would contain the files:

```
gamma.archive
```

```
gamma
```

```
gamma.map
```

and associated with the file `gamma.object` would be the additional names of all object files contained in `gamma.archive`.